


## WIRE-HOLDING STICK

The Chance Epoxiglas® Wire-Holding Stick is used on or around energized lines for forming, bending and positioning jumper wires; and for holding conductors during splicing operations. The gripper, equipped with an eye so that other sticks can assist with heavy bending, will handle No. 6 solid copper through 1590 kcmil ACSR.

Operation of the Wire-Holding Stick has been simplified so that it grips much like locking-type pliers. By tightening the knurled nut at the control lever, the wire-holding jaws can be positioned to firmly grip the conductor. When this is done, the tightening control lever must be relaxed in a position about 1 inch away from the pole. Then, to secure the grip on the conductor, push lever down to pole; and to release the conductor simply move the control lever all the way up along the rod.

The head of the tool locks in three stop positions so that the lineman can engage and position conductors easily from most angles. The knurled screw handle below the jaw opening is used to adjust the head position from straight to right or left.



Head of the tool locks in three positions . . . enables lineman to handle conductor from any angle.



With handle positioned as shown in square photo, above, the knurled nut can be turned to adjust the gripper to the exact wire size.

Conductor Capacity: #6 to 1590 kcmil ACSR (0.162" to 1.5")

Catalog No.	Pole Dia. & Overall Length	Approx. Weight
C4033068	1¼" x 6'5"	6½ lb./2.7 kg.
C4033069	1¼" x 8'5"	6¾ lb./3.0 kg.

**For SAFETYSHIELD™ Hot Stick Barrier to fit tools on this page, see page 2129.**

**Wire Holding Stick  
C4033068**

**Positive Grip  
Clamp Stick  
HG30302**

## Positive Grip Clampstick

The Epoxiglas Positive Grip Clampstick is made for use on eyescrew grounding or hot line clamps. It can be mounted on the line and tightened at angles up to 30°. Fittings are aluminum and bronze.

To install clamp, align locking ring with slot in housing; place eye of clamp into housing. Holding locking ring and clamp in one hand, rotate pole clockwise to trap eye. To remove clamp, engage locking ring on clamp body and rotate pole counter-clockwise to trap eye.

The butt end of the tool is equipped with a combination tool hanger and universal head.

Catalog No.	Pole Dia. & Overall Length	Type Head	Approx. Weight
HG30302	1¼" x 8'6"	Regular Length	4 lb./1.8 kg.
HG303012	1¼" x 8'6"	Extra Long	4 lb./1.8 kg.
HG30422	Reg. Length Clampstick Head Only		1 lb./0.45 kg.
HG30425	Extra Long Clampstick Head Only		1½ lb./0.5 kg.

**HG30425**

Extra long head (above) for use with long eyescrew ground clamps.