

Part No.

HPGV-0000

3000 psi (210 bar) HPGV pump, 1/4" female NPT gauge swivel, hose, process connection

Pressure source and gauge in one hand. Directly connect to a process connection and calibrate using your precision gauge.

Features

- Fine adjustment piston provides an easy way to fine tune exact pressure
- Vent valve is both durable and precise
- Liquid reservoir holds enough fluid for multiple calibrations
- Marine brass construction resists corrosion and abuse
- Quick-disconnect gauge adapter allows changing gauges without using a wrench
- Low volume Quick-test hose, gauge adapter and process connection can be attached to pump without thread sealant or a wrench

Item Includes

- Hand Pump - HPGV Assembly (HPGV)
- Gauge Adapter - 1/4" Female NPT swivel, brass (SWIV-2FBW)
- Hose - Quick-test hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, brass (QTHA-2MB0)

Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Media	Ralston Calibration Oil, mineral based oil, water
Outlet Port	Male Quick-test with check valve, brass
Temperature Range	0 to 130 °F (-18 to 54 °C)
Construction	Anodized Aluminum, Brass, Plated Steel
Seal Materials	Buna-N, Delrin, Synthetic Cork, Teflon
Fine Adjust Resolution	±1.00 psi
Liquid Reservoir	Polycarbonate Liquid reservoir and (2) gaskets
Weight	2.39 lb (1.1 kg)
Dimensions	H: 9.82 in (24.9428 cm) x W: 4.75 in (12.065 cm) x D: 4.75 in (12.065 cm)



HPGV-0000